



	PART NO.	WITH CV	DESCRIPTION	GAS SERVICE
<p>RIGID PIGTAILS, BRASS ACETYLENE & LPG SERVICE Pressure to 500 PSIG (3400 kPa)</p>  <p>P-15-PCV</p>	5/16" X .065" WALL BRASS TUBING 20" FINISHED LENGTH OVERALL			
	P-16	-	RH F Propane, Comm. Acet, Horiz.	CGA-300
	PV-15	-	LH M Propane, Brass, Horiz.	CGA-510
	P-15	P-15CV	LH M Propane, Mapp, Horiz.	CGA-510
	P-15-P	P-15PCV	LH M Pyrofax, POL Acet, Vert.	CGA-510

PART NO.	DESCRIPTION	GAS SERVICE	
HAND-TIGHT NUTS & NIPPLES * 5/16" x .065" WALL COPPER TUBE			<p>HAND-TIGHT RIGID PIGTAILS FOR PLANT OR FILLING STATIONS with Brass Connections Pressure to 3000 PSIG (20,700 kPa)</p>
PHC-320	RH F Carbon Dioxide	CGA-320	
PHC-326	RH F Nitrous Oxide	CGA-326	
PHC-346	RH F Air	CGA-346	
PHC-63	RH F Oxygen	CGA-540	
PHC-83	LH F Hydrogen	CGA-350	
PHC-92	RH M Nitrogen, Argon	CGA-580	
PHC-93	LH M Industrial Air	CGA-590	

	PART NO.	WITH CV	DESCRIPTION	GAS SERVICE
<p>STAINLESS STEEL RIGID PIGTAILS with Stainless Steel Connections * PRESSURES TO 3000 PSIG (20,700 kPa)</p> <p>Type 304 Stainless Steel Tube TIG Welded For Long Service Life Type 316 Stainless Steel Welded Fittings</p>  <p>Available In Straight Lengths</p> <p>Use With Either Stainless Steel Or Brass Connections</p>	1/4" x .049 WALL ST. STEEL TUBE TYPE 316 SS CGA FITTINGS			
	PS-320	-	Carbon Dioxide, RH F	CGA-320
	PS-346	-	Air, RH F	CGA-346
	PS-540	PS-540CV	Oxygen, RH F	CGA-540
	PS-580	PS-580CV	Nitrogen, Argon, RH M	CGA-580
	PS-590	-	Industrial Air, LH M	CGA-590

PART NO.		WITH CV	DESCRIPTION	GAS SERVICE
5/16" x .065" WALL COPPER TUBE, DOUBLE LOOP PRESSURES TO 3000 PSIG (20,700 kPa)				
PH-320	-		RH F Carbon Dioxide	CGA-320
PH-326	PH-326CV		RH F Nitrous Oxide	CGA-326
PH-346	PH-346CV		RH F Air	CGA-346
PH-63	PH-63CV		RH F Oxygen	CGA-540
PH-73	-		LH F Propane (Liquid With.)	CGA-555
PH-83	PH-83CV		LH F Hydrogen	CGA-350
PH-92	PH-92CV		RH M Nitrogen, Argon	CGA-580
PH-93	-		LH M Industrial Air	CGA-590
5/16" x .065" WALL BRASS TUBE, SINGLE LOOP PRESSURES TO 500 PSIG (3400 kPa)				
PH-300	-		RH F Commercial Acetylene	CGA-300
PH-510	-		LH M POL Acetylene	CGA-510

**RIGID PIGTAILS,
BRASS FORGED HANDLE
with Brass Connections**

PH-68CV

PART NO.		WITH CV	DESCRIPTION	SERVICE
MANIFOLD RIGID PIGTAILS, COPPER TUBING with Brass Connections PRESSURES TO 3000 PSIG (20,700 kPa)				
ANNEALED 5/16" x .065" WALL COPPER TUBE				
P-CO-3	-		RH F, Carbon Dioxide	CGA-320
P-63	P-63CV		RH F, Oxygen	CGA-540
P-73	-		LH F, Propane (Liquid With.)	CGA-555
P-83	P-83CV		LH F, Hydrogen	CGA-350
P-92	P-92CV		RH M, Nitrogen, Argon, Helium	CGA-580
P-93	-		LH M, Industrial Air	CGA-590
P-1320	P-1320CV		RH F, Nitrous Oxide	CGA-326
P-1340	P-1340CV		RH F, Air	CGA-346

P92-CV

PART NO.	DESCRIPTION	SERVICE
ANNEALED 5/16" x .065" WALL COPPER TUBE		
PV-CO-3	RH F, Carbon Dioxide	CGA-320
PV-1340	RH F, Air	CGA-346
PV-63	RH F, Oxygen	CGA-540
PV-92	RH M, Nitrogen, Argon, Helium	CGA-580

**RIGID PIGTAILS, COPPER
TUBING, BRASS SHUTOFFS
with Brass Connections
PRESSURES TO 3000 PSIG (20,700 kPa)**

PV-92

PART NO.	DESCRIPTION
STAINLESS STEEL RIGID PIGTAILS PRESSURES TO 6000 PSIG (41,300 kPa)	
	1/4" Female Both Ends
PS-4-36	36" Length, Straight
PS-4-48	48" Length, Straight
PS-4-60	60" Length, Straight